

# SPECIFICATION SHEET



## ACCENT TWO HANDLE LAVATORY WIDESPREAD FAUCET



**Model #:** \_\_\_\_\_  
**Specific Features:** \_\_\_\_\_  
**Project Name:** \_\_\_\_\_  
**Submitted For:** \_\_\_\_\_  
**Date:** \_\_\_\_\_

- Lever Handles
- 'C' Style Spout
- 4-9/16" Reach, 1-7/8" From Deck to Aerator
- Washerless Cartridge Operation
- 3-Hole 4" to 16" Installation
- 50/50 Pop-Up Drain Assembly


# L-7330 SHOWN **ADA**

Model #	Features	Finish	
L-7330		CP	
L-7330-BN		PVD BN	
L-7330-ORB		ORB	
L-7330-E1.5	1.5 GPM Flow Rate	CP	

Olympia products are engineered and manufactured to meet the following standards and codes:

- ASME A112.18.1
- ANSI A117.1
- ANSI / NSF 61, SECTION 9
- IAPMO LISTED
- CONTAINS NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT

- Note:
1. Mounting surface hole size to be 1-1/4".
  2. Max. mounting deck thickness to be 1-1/8".



50/50 Pop-Up Drain